








# TIMESPACE TECHNOLOGY

## DVR PRODUCT SELECTOR



	V600	V500	V400	X500	X300	X300-16M	R500
<b>Features</b>							
<b>Video</b>							
PAL video inputs	12 or 16 or 20	16	8 or 12 or 16	4	4	16	4
AHD video inputs	combined PAL/AHD*	0	0	0	0	0	0
IP Video inputs	4	8 PoE	1	4 PoE	0	0	4**
IPS max per camera (PAL/NTSC)	25 (PAL)	25/30	25/30	25/30	25/30	25/30	25/30
IPS global (PAL)	Up to 200 (PAL)	200	100/120 or 150/180 or 200	100	200/240	200/240	100
Video compression	H264	H264	H264	H264	MPEG2	MPEG2	H264
Video resolution IP Cameras	720P, 1080P	1080p	1080p	4k	n/a	n/a	4k
Video resolution PAL Cameras	2CIF	2CIF	2CIF	2CIF	D1	D1	2CIF
Video resolution AHD Cameras	720P, 1080P	n/a	n/a	n/a	n/a	n/a	n/a
Video Outputs	2	4	2	2	1	2	1
<b>Audio</b>							
Audio inputs	2	2	2	1 + 4 High Quality	2	1	1
Audio quality	16 bit	16 bit	16 bit	1 x 16 bit & 4 x 24 bit	16 bit	16 bit	16 bit
<b>Features</b>							
Alarm in	10	10	10	6	5	10	10
Alarm out	4	4	4	3	3	3	1
Motion detection	no	No	No	✓	✓	✓	No
Recording watermark	✓	✓	✓	✓	✓	✓	✓
File p/word protection & encryption	✓	✓	✓	✓	✓	✓	✓
Power-down timer	✓	✓	✓	✓	✓	✓	✓
Built-in camera power/connector	Yes/Neutrik 3-way	Yes/Neutrik 3-way	Yes/Neutrik 3-way	No	No	Yes/Molex	Yes/GX12 4-way
Configurable alarm switching	✓	✓	✓	✓	✓	✓	✓
PTZ Support	No	✓	✓	✓	✓	✓	✓
GPS Input	✓	✓	✓	✓	✓	✓	✓
RTSP streaming***	✓	✓	✓	✓	No	No	Yes
Built-in GSensor	✓	✓	✓	✓	No (separate reqd)	✓	✓
<b>Connectivity</b>							
POE	No	✓	No	✓	No	No	No
Supports CANLink	Built-in	✓	✓	No	✓	✓	✓
Supports Bridge Alert	✓	✓	✓	No	No	No	No
<b>Physical Characteristics</b>							
IP rating	IP50	IP50	IP50	IP50	IP50	IP50	IP50
Dimensions l x w x h (mm)	292x126x151	292x132x143	292x132x143	206x136x53	210x120x50	210x120x50	206x136x53
Voltage input	12-48V	12-40V	11-50V	10-30V	12V	12V	10-30V
<b>Conformance/Approvals</b>							
VCA Approval /E-Mark	✓	✓	✓	No	✓	✓	✓
R118 approval (Fire retardancy)	✓	✓	✓	✓	✓	✓	✓
CE conformity	✓	✓	✓	✓	✓	✓	✓

\*a maximum numbers of 1080P AHD cameras applies

\*\*the R500 can also support up to 16 additional IP cameras by use of external switches

\*\*\*RTSP is not included as standard but can be activated under licence and requires LANLink

All DVRs have a removable hard drive (max 4TB), removable SD card, and option of solid state disk (max 2TB)

All DVRs are compatible with Timespace Reviewer and PCLink and LANLink software